



## Electro-hydraulic Directional Control Valve

External dimensions ( 10 Alternating current wire box type )



### 10 Size of subplate oil port



## Manual operated Directional Control Valve

Technical specification




Specification	02	03	04	06
Working pressure ( MPa)	Port P、A、B	31.5		
	Port T	10		
Max. Flow (L/min)	60	100	300	450
Working fluid	Mineral oil; phosphate-ester			
Fluid temp. (°C)	-20~70			
Viscosity (mm <sup>2</sup> /s)	2.8~380			
Weight (kg)	About 1.4	About 3.3	About 8	About 17
	The maximum allowable cleanliness of the oil should be according to 9th degree of Standard NAS1638. It is suggested that the minimum filter rating should be β 10≥75.			

Manual operated directional control valve is a directional control valve, by operating the handle, the spool moves in the axial direction to achieve oil loop switching.

Manual operated directional control valve and electrical operated directional control valve are played the same role in the hydraulic system. Easy operation, reliable work, and without the need for electricity.

### Model description




# Manual Operated Directional Control Valve

## Code symbol

Spring return			
With detent			


# Manual Operated Directional Control Valve

## The relationship between the location of the handle and the direction of the oil flow



1. The name of the handle as shown in the picture
2. When the handle is on position b P→B A→T
3. When the handle is on position a P→A B→T
4. Oil flow in the opposite direction with the above-mentioned movement for 02/03:3C5,3C6.  
Oil flow in the opposite direction with the above-mentioned movement for 04/06:3C6.
5. For specification 03 spool type 2B2L,2B3L, 2B8L, the handle is at the side of port B, details refer to the external dimension

## 02 Specification Performance curve ( Measured at $v=41\text{mm}^2/\text{s}$ and $t=50^\circ\text{C}$ )




Function code	Direction			
	P→A	P→B	A→T	B→T
2B8 2B8L	3	3	-	-
2B3	1	1	3	1
2B2 2B2L	5	5	3	3
3C2	3	3	1	1
3C5	1	3	1	1
3C6	6	6	9	9
3C3	2	4	2	2
3C4	1	1	2	1
3C10,3C12	3	3	4	9
3C9	2	3	3	3
3C25	3	1	1	1
3C29	5	5	4	-
3C7	1	2	1	1

7. Spool type "3C29" located in the control position A→B
8. Spool symbol 3C6 in the neutral position P→T

# Manual Operated Directional Control Valve

## 02 Specification Working limits (The working limits for directional valve have determined by using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank.)

As the plug, the switch function of the valve is determined by the filter. In order to reach the largest flow as shown, we suggest to use full-flow filter 20 μm. Every force on the valve can also affect the flow. With regard to the four-way valve, the normal flow data as shown is get from the regular use of two directions of the flow (e.g.P to A, and simultaneous return flow from B to T). See tables. If only one flow direction is needed, for example: When a four port valve which is closed up port A or port B, used as a three-way valve, the Maximum flow may be very small in the serious condition.




4.Spool symbol "3C6" in the median position P to T  
7.Spool symbol "3C29" in the control position A to B

Performance curve	Function code	Performance curve	Function code	
Without detent	1	With detent	1	
	2		2	
	3		3	
	4		4	
	3C2 3C3 2B3 2B2			5
	3C9 3C10			6
	3C6 3C4			7
	3C12 3C29 2B2L			8
	2B8 2B8L			
	3C7			
	3C5 3C25			

# Manual Operated Directional Control Valve


## 03 Specification Performance curve ( Measured at $v=41\text{mm}^2/\text{s}$ and $t=50^\circ\text{C}$ )



	P→A	P→B	A→T	B→T
2B8	2	2	-	-
2B8L	2	2	-	-
2B3	2	2	3	3
2B2	2	2	3	3
3C2	2	2	4	4
3C5	2	3	3	5
3C6	3	3	4	6
3C3	1	1	4	5
3C4	2	2	3	3
3C12	2	2	3	5
3C9	1	1	5	5
3C25	3	2	5	3
3C29	2	4	3	-
3C10	2	2	3	5
3C7	2	2	4	4
2B2L	2	2	5	3

4.Spool symbol 3C6 in the neutral position P → T  
7.Spool type "3C29" located in the control position A → B


## Working limits (The working limits for directional valves have determined by using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank.)



1	2B8 2B8L
2	3C3
3	3C5 3C6 3C25 3C29
4	3C4 3C12 3C10
5	2B2 2B3 3C2 3C9 3C7 2B2L

# Manual Operated Directional Control Valve

## 04 Specification Performance curve ( Measured at $v=41\text{mm}^2/\text{s}$ and $t=50^\circ\text{C}$ )




Function code	Direction			
	P→A	P→B	A→T	B→T
3C2 2B2 2B2L	1	1	1	3
3C5	2	2	3	3
3C6	5	1	3	7
3C3 2B3	2	2	3	3
3C7	2	2	3	3
3C4 3C12	1	1	3	3
3C29	2	2	4	-
3C10	2	2	4	-
3C	1	1	4	7

6. Spool symbol 3C6 in the neutral position P → T

# Manual Operated Directional Control Valve

## 06 Specification Performance curve ( Measured at $v=41\text{mm}^2/\text{s}$ and $t=50^\circ\text{C}$ )



Function code	Direction			
	P→A	P→B	A→T	B→T
3C2	2	2	1	4
3C5	1	2	1	2
3C6	2	2	2	4
3C3	2	2	1	3
3C4	2	2	1	3
3C12	2	2	1	2
3C9	2	2	1	4
3C25	2	2	1	4
3C29	1	2	1	-
3C10	2	2	1	4
3C7	2	2	1	4

4. Spool symbol "3C12" in the neutral position A → T  
6. Spool symbol "3C10" in the neutral position B → T

## 04 Specification Working limits (The working limits for directional valves have determined by using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank.)

4/2 valve Without detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
2B3	300	300	300	260	220
2B2	300	300	210	190	160

4/2 valve With detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
2B2 2B3	300	300	300	260	220

4/3 valve Without detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
3C2 3C3 3C4 3C12 3C9 3C29 3C10	300	300	300	300	300
3C5 3C25	300	300	210	190	170
3C6	300	300	220	210	180
3C7	300	260	200	180	170

4/3 valve With detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
3C2 3C3 3C4 3C12 3C9 3C29 3C10	300	300	300	300	300
3C5 3C25	300	300	280	230	230
3C6	300	300	230	230	230
3C7	300	300	250	230	230

## 06 Specification Working limits (The working limits for directional valve have determined using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank.)

4/2 valve Without detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
2B3	450	300	250	200	180
2B2	350	300	275	250	200


4/2 valve With detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
2B3 2B2	450	450	450	450	450

4/3 valve Without detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
3C2 3C3 3C4 3C12 3C9 3C29 3C10	450	450	450	450	450
3C5	450	250	200	135	110
3C6	450	330	290	230	180
3C3	450	450	400	400	350
3C25	450	310	240	215	150
3C7	450	310	280	270	200

4/3 valve With detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
3C2 3C5 3C6 3C3 3C4 3C10 3C9 3C25 3C29 3C12	450	450	450	450	450
3C7	450	450	400	350	300

# Manual Operated Directional Control Valve

## 10 Specification Performance curve ( Measured at $v=41\text{mm}^2/\text{s}$ and $t=50^\circ\text{C}$ )




Function code	Direction				
	P→A	P→B	A→T	B→T	P→T
3C2	1	1	2	3	-
3C6	6	5	6	7	7
3C29	1	1	2	-	4

10 All other spool types

# Manual Operated Directional Control Valve

## 02 External dimensions



## 10 Specification Working limits (The working limits for directional valves have determined by using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank.)


4/2 valve Without detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
2B3	1100	1040	860	800	700
2B2	1100	1040	540	480	420

4/2 valve With detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
2B3 2B2	1100	1040	860	750	680

4/3 valve Without detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
3C2 3C3 3C4 3C12 3C9 3C29 3C10	1100	1040	860	750	680
3C5	900	900	800	650	450
3C6	900	900	800	650	450
3C3	900	900	800	650	450
3C25	900	900	800	650	450
3C7	1100	1100	680	500	450

4/3 valve With detent					
Function code	Working pressure (MPa)				
	7	14	21	28	35
Flow ( L/min )					
3C2 3C5 3C6 3C3 3C4 3C10 3C9 3C25 3C12	1100	1040	860	750	680
3C7	1100	1040	860	750	680

## 02 Size of subplate oil port




Mounting screw	Amount	Tighten torque
M5x50-10.9	4	9Nm

### Supplementary explanation

- When installing the product, considering horizontal position firstly.
- The medium used in the hydraulic system must be filtered, its accuracy is at least  $20\mu\text{m}$ .
- Screw should be according to the parameters in catalogue.
- The surface, connecting with the valve, should be Ra0.8 roughness, and 0.01/100mm flatness.

# Manual Operated Directional Control Valve


## 03 Spring type external dimensions



D.7.10


# Manual Operated Directional Control Valve

## 03 With detent type external dimensions




D.7.11

## 03 Spring type size of subplate oil port




## 03 With detent type size of subplate oil port



# Manual Operated Directional Control Valve


## 04 External dimensions



D.7.12


# Manual Operated Directional Control Valve

## 06 External dimensions



D.7.13


## 04 Size of subplate oil port



Mounting screw	Amount	Tighten torque
M6x55-10.9	2	15Nm
M10x60-10.9	4	75Nm

- Supplementary explanation
- When installing the product, considering horizontal position firstly.
  - The medium used in the hydraulic system must be filtered, its accuracy is at least 20 μm.
  - Screw should be according to the parameters in catalogue.
  - The surface, connecting with the valve, should be Ra0.8 roughness, and 0.01/100mm flatness.

## 06 Size of subplate oil port



Mounting screw	Amount	Tighten torque
M12x60-10.9	6	130Nm

- Supplementary explanation
- When installing the product, considering horizontal position firstly.
  - The medium used in the hydraulic system must be filtered, its accuracy is at least 20 μm.
  - Screw should be according to the parameters in catalogue.
  - The surface, connecting with the valve, should be Ra0.8 roughness, and 0.01/100mm flatness.